

Total No. of Printed Pages:2

SUBJECT CODE NO:- E-28
FACULTY OF ENGINEERING AND TECHNOLOGY
T.E.(CIVIL) Examination Nov/Dec 2017
Design of Structures - II (RCC)
(REVISED)

[Time: Three Hours]

[Max.Marks:80]

Please check whether you have got the right question paper.

- N.B
1. Q.No.1 and Q.No.6 are compulsory. Answer any two from Section A & Section B.
 2. Assume suitable data if necessary.
 3. Figures to right indicate the maximum marks.
 4. Use of non-programmable calculator is allowed.
 5. Use of IS: 456-2000 is permitted.

Section- A

- Q.1 a) What are the advantages and disadvantages of Providing Large Clear cover to Reinforcement in Flexural Member. 03
- b) Enumerate the different types of Limit State with Brief Description. 04
- c) Why is the Provision of Minimum Reinforcement in Reinforced Concrete Beam? 03
- Q.2 Design Simply Supported beam of span 5M. is to carry A Uniform Dead Load of 20 KN/M. and Uniform Live Load of 30KN/M. the width of the support is 230mm. assume M-25 Concrete and Fe-415 steel. 15
- Q.3 Design Cantilever beam of span 3-0 Mt. is to carry A Uniformly Distributed Load of 20 KN/M. the width of the support is 230 mm. assume M-25 Concrete and Fe-500. Show the curtailment of reinforcement. 15
- Q.4 a) What is mean by cracking? Explain the types of cracks. 03
- b) A rectangular beam of span 6M c/c resting on 300 mm wide simple supports is to carry a Superimposed load of 35 KN/M. design the Beam it is Restricted to 450 MM. Use M20 and Fe 415 Grade. 12
- Q.5 An Isolated Simply supported T-Beam has flange width 2300 MM and Flange thickness of 120 MM, the effective span of the beam is 3.5 Meter. The effective depth of the Beam is 580 MM and width 300MM. The Beam having the Reinforcement with 8-20 MM Tor Use M20 and Fe 415 Grade Determine the Moment of Resistance of the section. 15

Section- B

- Q.6 Explain the following terms. 10
- a) Development length and necessity of the check.
 - b) Necessity of torsion reinforcement in the slab.
 - c) Relationship for the load carrying capacity of an axially loaded short column.
 - d) One-way slab and two-way slab.
- Q.7 Design a reinforced concrete slab for a room $4.2\text{M} \times 6.0\text{M}$ supported on a beam of width 250MM. 15
the slab is continuous over right support and down ward direction in plan, carrying a live load of 3KN/M^2 & floor finish 1.0 KN/M^2 . Assume M-25 grade concrete & Fe-415 grade steel.
- Q.8 Design a dog legged stair case for a residential building having a room size $5\text{m} \times 2.5\text{M}$. Floor to 15
floor height is 3M. The column size $230\text{MM} \times 380\text{MM}$ located at four corners take live load 3KN/M^2 & floor finish load 0.9 KN/M^2 . Use M20 and Fe-415 grades.
- Q.9 Design isolated footing for rectangular column $230\text{mm} \times 600\text{mm}$ reinforced with 8 bars of 25 mm 15
diameter. And carrying axial load of 1200 KN, SBC of soil is 250 KN/M^2 at a depth of 2.0 m below ground level. Assume M-25 grade of concrete & Fe-415 grade of steel.
Show the reinforcement in details.
- Q.10 Design a rectangular column subjected to ultimate load of 2500KN. The column is 4.0M long & 15
effectively held in position at both ends but not restrained against rotation.
Take M-20 & Fe-500 grades.